

Clack Filter-Ag is a non-hydrous silicon dioxide media which can be used as highly efficient filter media for the reduction of suspended matter.

Filter-Ag®

ADVANTAGES

- There is less pressure loss through a bed of Filter-Ag® than through most other filter medias
- Light weight requires lower backwash rates than those required for other filter medias
- High service rates result in lower equipment costs and a savings in space
- High sediment reduction capacity results in longer filter runs, with a substantial savings in backwash water and time out of service
- Reduced shipping cost due to light weight/cu. ft.
- Replacement of sand with Filter Ag in existing installations may increase filter capacity 100% or more. (Caution should be taken upon start-up that the lightweight Filter-Ag is not washed to drain.)

PHYSICAL PROPERTIES

- Color: Light grey to near white
- Bulk Density: 24-26 lbs./cu. ft.
- Specific Gravity: 2.25 gm/cc
- Mesh Size: 12 x 30
- Effective Size: 0.67 mm
- Uniform Coefficient: 1.8
- Hardness: 6 (Mohs scale)

CONDITIONS FOR OPERATION

- Water pH range: wide range
- Maximum water temperature: 140°F/60°C
- Bed depth: 24-36 in.
- Freeboard: 50% of bed depth (min.)
- Service flow rate: 5 gpm/sq. ft., although considerably higher rates are often used
- Backwash flow rate: 8-10 gpm/sq. ft.
- Backwash bed expansion: 20-40% of bed depth
- Upon installation allow bed to soak overnight before backwashing



Clack Filter-Ag® has many outstanding advantages over the more common granular filter medias used for suspended solids reduction. Its fractured edges and irregular surface provides a high surface area and complex flow path for efficient removal of suspended matter through out the filter bed, typically reducing suspended solids down to the 20-40 micron range. Filter-Ag's larger particle size creates less pressure loss through the filter and allows deeper sediment penetration into the bed for higher sediment loading and longer filter runs. This large and irregular shape prevents the screening and caking of sediment in the top several inches of the filter bed as happens in the typical sand filter, thus preventing a rapid build up of headloss and blinding problems. Filter-Ag's light weight means lower backwash rates and better bed expansion to release trapped sediment and rinse the filter media during the backwash cycle. This ideal combination of particle shape, size and density make it a good choice where quality water filtration and water conservation are important.

Although not intended to be an iron reduction media, extensive field experience has shown Filter-Ag's rough and jagged surface to be very good at entrapping the fragile iron flock that forms after dissolved iron has been oxidized. The fragmented edges are apparently good flock collection points for the precipitated iron. Typical oxidation methods include aeration, ozonation and chlorination.

Substantial savings can be realized when designing a system using Clack Filter-Ag. Its low pressure drop, high service flow rates and high bed loadings combined with lower backwash rates allow economy in equipment downsizing and reduced pumping requirements. Its light apparent density also saves on handling expense and shipping costs.

Clack Filter-Ag can be applied to systems designed for either pressure or gravity flow. Because of its unique density, Filter-Ag can also be used in multi-media (graded density) filter designs allowing a more flexible approach to difficult filtration problems.





Drinking Water Treatment System
 Components Classified by
 Underwriters Laboratories Inc.® in
 Accordance with Standard
 ANSI/NSF 61-(1991)-57Y3

ORDER INFORMATION

Part No.	Description	Cu. Ft./Bag	Wt./Cu. Ft.*	Bags/Pallet	Weight/Pallet	Pallet Dimensions
A8014	Filter Ag®	1	25 lbs.	70	1800 lbs.	48" x 40" x 64"

*Weight per cubic foot is approximate.

Clack Corporation
 4462 Duraform Lane PO Box 500
 Windsor, Wisconsin 53598-0500 USA
Phone (608) 846-3010
 Fax (608) 846-2586
 Sales Fax (800) 755-3010
www.clackcorp.com

Form No. 2351
 Replaces Form 1564
 Updated 2/99

Filter-Ag® is a federally registered trademark of Clack Corporation.

The information and recommendations in this publication are based on data we believe to be reliable. They are offered in good faith, but do not imply any warranty or performance guarantee, as conditions and methods of use of our products are beyond our control. As such, Clack makes no express or implied warranties of any kind with respect to this product, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. We recommend that the user determine whether the products and the information given are appropriate, and the suitability and performance of our products are appropriate, by testing with its own equipment.

The information and recommendations given in this publication should not be understood as recommending the use of our products in violation of any patent or as a license to use any patents of the Clack Corporation.

The filter medias listed in this brochure do not remove or kill bacteria. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Clack will not be liable under any circumstance for consequential or incidental damages, including but not limited to, lost profits resulting from the use of our products.